

FICHA TÉCNICA

VSG136K

6


FA 30 600 XX

P. 1 | 2



FA 30 600 10
FA 30 600 15

①



FA 30 600 13










①



HS CODE
56090090
CARTON SIZE / PCS.
60 x 40 x 24 cm / 12
AET N°2777/10964-01/E06-01
Satra Technology Europe Ltd., N° 2777, Bracetown Business Park, Clonee, Dublin, D15YN2P, Ireland
MODULE D F14/14003.02
SGS Fimko Oy, N°0598 Takomotie 8, 00380 HELSINKI, Finland
AET (UKCA) N°AB0321/16096-01/E01-01
Satra Technology Centre, N°0321 Wyndham Way, Telford Way, Kettering Northamptonshire, NN16 8SD, United Kingdom
MODULE D 11 IN14/14003
SGS United Kingdom Ltd., N°0120 Unit 202B, Worle Parkway, Weston-super-Mare, BS22 6WA, United Kingdom

Frimsal Distribuciones, S.L.

Avda. Canaletes, 45 - 08290 Cerdanyola (Barcelona)
C/ Repostería, 7 - Pgno. Ind. San Rafael - 41620 Marchena (Sevilla)
Telf. 902 125 661 - Fax. 902 102 156 - E-Mail; info@frimsal.es
<http://www.frimsal.com>

REF.	FA 30 600 13	FA 30 600 10	FA 30 600 15
LG.  KG	1.3 m	1 m (connectors included)	1.5 m (connectors included)
CE	Max. 100 KG		
MAT.	EN 355:2002		
	● PA 11 mm		
	45 mm		
	---		
+	NO		
	PPE-R 11.063		
KG	0.74 KG	1.60 KG	1.82 KG



Largeur de l'absorbeur d'énergie
Width of the energy absorber
Ancho del absorbedor de energía
Larghezza del assorbitore di energia
Breite des Falldämpfers

LG.



Longueur Poids maxi utilisateur
Length Max. user weight
Longitud Peso máximo del usuario
Lunghezza Peso Max. dell'utente
Länge Höchstgewicht des Benutzers



Matière connecteur haut / connecteur bas
Material of top connector / bottom connector
Material conector alto / conector bajo
Materiale connettore alto / connettore basso
Material oberes / unteres Verbindungselement



Ouverture
Gate opening
Apertura
Apertura
Öffnung



Homologué pour le travail à proximité d'arêtes vives
Approved for work near sharp edges
Homologado para trabajo cerca de aristas vivas
Omologato per lavoro in prossimità di spigoli vivi
Zugelassen für Arbeiten in der Nähe scharfer Kanten