

FICHA TÉCNICA

VSG312C



FA 20 402 10B, FA 20 402 10S

P. 1|2

Helixon



①




②



③



④











| |
|---|
| HS CODE |
| 84798997 |
| CARTON SIZE / PCS. |
| 60 x 40 x 24 cm / 4 |
| AET N°2777/10832-02/E01-01 |
| Satra Technology Europe Ltd., N° 2777, Bracetown Business Park, Clonee, Dublin, D15YN2P, Ireland |
| MODULE D F114/14003.02 |
| SGS Fimko Oy, N°0598 Takomotie 8, 00380 HELSINKI, Finland |
| ACKNOWLEDGEMENT OF RECEIPT N°3975/1/2018 (ATEX) |
| Technická Inšpekcia, a.s. N°1354 Trnavská cesta 56, 821 01 Bratislava, Slovenská Republika |

Frimsal Distribuciones, S.L.

Avda. Canaletes, 45 - 08290 Cerdanyola (Barcelona)
C/ La Ventilla, 37 - 41620 Marchena (Sevilla)

Telf. 902 125 661 - Fax. 902 102 156 - E-Mail; info@frimsal.es

<http://www.frimsal.com>


| REF. | FA 20 402 10B | FA 20 402 10S |
|--|--|---|
| LG.  KG | 10 m | |
| CE | EN 360:2002 | |
| MAT.  | Polyamide 6 - 30% fiber glass | |
|  |  STEEL Ø4.5 mm |  SNOX Ø4.5 mm |
|  | FA 50 101 17 / FA 50 203 20 with fall indicator | FA 50 101 17 / stainless steel connector with fall indicator |
| R(kN) | 12 kN | |
|  | NO | |
| + | Ex II 2 Exh IIC T6 Gb EN 360 §4.6 (endurance test) | |
|  | 4.27 KG | 4.28 KG |

LG.
KG

Longueur Poids maxi utilisateur
Length Max. user weight
Longitud Peso máximo del usuario
Lunghezza Peso Max. dell'utente
Länge Höchstgewicht des Benutzers

MAT.


Matière carter / câble
Material of casing / wire rope
Material cárter / cable
Material dei carter / cavo
Material Gehäuse / Seil



Matière connecteur haut / connecteur bas
Material of top connector / bottom connector
Material conector alto / conector bajo
Materiale connettore alto / connettore basso
Material oberes / unteres Verbindungselement



Nombre d'émerillons
Number of swivels
Cantidad de eslabones giratorios
Numero di tornichetti
Anzahl der Wirbel



Homologué pour le travail à proximité d'arêtes vives
Approved for work near sharp edges
Homologado para trabajo cerca de aristas vivas
Omologato per lavoro in prossimità di spigoli vivi
Zugelassen für Arbeiten in der Nähe scharfer Kanten